

Rhino Fiber Curve™

Fiberglass Marker Post

Fact Sheet




The Rhino FiberCurve concave design allows the post to flatten out completely when hit, then snap back into its normal upright position. The Rhino FiberCurve will even withstand a direct hit from a tire at 55 mph.

The Rhino FiberCurve is saturated with bright pigments, and UV stabilizers are added to ensure the color remains bright for years. For an extra layer of protection, we add our clear SunCoat™ over the entire surface of the post.

Description:

- Standard lengths: 62" | 72"
- Width: 4"
- Fiberglass set in a composite resin
- Side-rails and reinforcing rib provide strength and rigidity
- Temperature stable
- Pointed end for easy installation in most soil conditions
- Can withstand impacts from front or back and return to standing position
- Remains flexible from -40° F to +140° F.
- *Generic or custom decals may be applied to front and back
- 10-year surface warranty for posts that include our patented PolyTech Coating™

Standard Post Colors



	Prevents Fading	Completely Blocks UV Light	Prevents Fiberbloom	10-Year Warranty
SunCoat	✓	✗	✗	✗
PolyTech Coating™	✓	✓	✓	✓

Options & Add-Ons

PolyTech Coating™

Our patented coating which totally blocks ultraviolet light from the surface of the post. This optional coating replaces the SunCoat™ and is the same color as the post.



Flat Post Anchor Barb
(Helps prevent vandalism)
Part# AB-FCP-KIT



Universal Flat Post Driver
Part# RHD-44-A



Pilot Hole Driver for hard/rocky soil conditions
Part# PHD-100-A