



RFID Emergency Equipment Tags

Fact Sheet

Part#s: WF-SM-EED



Quickly identify and confirm expiration dates of emergency equipment within the cabin and cargo hold during maintenance scan from up to 30 ft. The Dual Record RFID Emergency Equipment Tags are provided as a blank tags for OEMs or airlines to print and encode their own EPC and Spec 2000 User Memory data.

These tags can be easily attached using cable tie, safety wire or with the adhesive strip on the back. They are typically used specifically in the aviation industry and conform to SAE AS5678A.

The Dual Record RFID Emergency Equipment Tag can be customized with corporate information, text or barcodes. They can also be pre-encoded. The permanent acrylic adhesive adheres to a variety of surfaces, including LSE materials.

DESCRIPTION:

- Compliance: SAE AS5678A / ATA Spec 2000
- Adhesive: 3M 9672LE
- Read Range: 30 ft.
- Application: Indoor
- Durability: Moisture, Oil and Solvent resistant
- Service Temperature Range: -40°F to 200°F
- Storage Temperature: 77°F for 1 Year
- Frequency: 860 – 960 MHz (Global)
- Tag Type: Passive Read/Write
- Barcoding Options:
 - Code 39 / Code 128
 - 2D Data Matrix
 - QR Code
 - Micro QR Code
- RFID Protocol: EPC Class 1 Gen 2; ISO 18000-6C

